



VPL-3200B Residential Vertical Platform Lift Technical Specifications

rev: 10/17/2011
ILS-00986

MODEL NUMBER: VPL-3200B Series: *Models VPL-3210B, VPL-3212B and VPL-3214B (DC-powered units)*
U.S. F.D.A. CLASSIFICATION: Class II
CLASSIFICATION NUMBER: 890.3930
PRODUCT CODE: ING
CSA/C-US Listed: File Number 208135

PERFORMANCE STANDARDS:

ANSI/ASME: A18.1-1999 (Sec. 5) Safety Standards for Platform Lifts and Stairway Chairlifts
ANSI/ASME: A18.1-2003 (Sec. 5) Safety Standards for Platform Lifts and Stairway Chairlifts
ANSI/ASME: A18.1-2005 (Sec. 5) Safety Standards for Platform Lifts and Stairway Chairlifts
ANSI/ASME: A18.1-2008 (Sec. 5) Safety Standards for Platform Lifts and Stairway Chairlifts
CSA B613 Private Residence Lifts for Persons with Physical Disabilities
ANSI/ASME: CSA B44.1/ASME-A17.5 Elevator and Escalator Electrical Equipment

RATED LOAD: 750 lb (340 kg) maximum

NUMBER OF PASSENGERS: 1 passenger with mobility device

DRIVE:

- **DC battery-powered units:**
 - *primary drive: 1 hp motor, 1750 rpm, 24VDC permanent magnet, 20 full-load amps, continuous duty*
 - *5A, 24VDC output internal battery charger, 120VAC, 60 Hz, 3A maximum input power required*

INTERMEDIATE REDUCTION: dual 4L style poly-V belts and pulleys, 3.94:1 pulley reduction

FINAL DRIVE: 1 1/4" (32 mm) diameter Acme screw with bronze nut and bronze safety back up nut

MOTOR CONTROLLER:

- **DC battery-powered units:** *24VDC relay control with 60A circuit breaker and disconnect*

BRAKING:

- **DC battery-powered units:** *precision landing control*

STANDARD CONTROL: separate up and down pushbutton switches or paddle controls, continuous pressure, key switch control

EMERGENCY STOP SWITCH: (*standard*) red, sealed, 1.55" (39 mm) diameter mushroom head, push to stop, pull to reset; (*optional*) red, sealed, 1.55" (39 mm) diameter mushroom head, illuminated with audio alarm, push to stop, pull to reset

SPEED:

- **DC battery-powered units:** *10 ft/min (0.05 m/s) maximum*

LIFTING HEIGHT: model VPL-3210B: 123" (3124 mm) maximum floor-to-floor height;
model VPL-3212B: 147" (3734 mm) maximum floor-to-floor height;
model VPL-3214B: 171" (4343 mm) maximum floor-to-floor height

For pit applications, maximum floor-to-floor is measured from the bottom of the pit.

Bruno Independent Living Aids, Inc., 1780 Executive Drive, P.O. Box 84, Oconomowoc, WI 53066
Phone (800) 882-8183 Fax (262) 953-5501

Any reproduction or other use of these materials without written permission of Bruno Independent Living Aids, Inc. is expressly prohibited.
Bruno Independent Living Aids, Inc. reserves the right to modify or make changes to these specifications at any time without notice.

MAIN FRAME CONSTRUCTION: welded steel tubular guide construction with formed sheet steel guarding

CARRIAGE CONSTRUCTION: welded carriage with 2.25" (57 mm) diameter front and back sealed dual-ball-bearing wheels and adjustable low-friction plastic side stabilizer guide pads

PLATFORM CONSTRUCTION: totally enclosed side walls consisting of 1" (25 mm) tubular framing and sheet metal siding

UNDER CARRIAGE SAFETY: totally enclosed bottom formed steel safety pan

AUTOMATIC LOWER RAMP: 16" (406 mm) long self lowering ramp (standard on unenclosed applications)

EMERGENCY LOWERING: external lockable keyed switch for lowering platform by means of a separate battery located inside the electrical enclosure

FINISH: exterior grade powder coat paint

LIMIT SWITCHES: adjustable upper and lower limit switches; upper final limit switch

MANUAL LOWER DEVICE: optional; manual hand crank to lower device available; access to adaptive shaft via safety interlocked top cap

REMOTE CONTROL: optional; station includes a separate landing call and send pushbutton switches or paddle controls and a keyed on/off switch

TOP LANDING GATE: optional; includes Bruno mechanical interlock which releases door, only when platform is at upper landing; electronic sensors stop platform from operating unless door is closed; also includes call/send pushbutton switches or paddle controls and keyed on/off switch mounted into gate frame

PLATFORM GATE: optional; includes Bruno mechanical interlock which releases door, only when platform is at lower landing. Electronic sensors stop platform from operating unless door is closed

FLUSH MOUNT DOOR: optional; includes Von Duprin® electronic interlock which releases door only when platform is at door landing; electronic sensors stop platform from operating unless door is closed; offered as an oak door with steel frame (no fire rating) or a steel door with steel frame (90 min. fire rating including a viewing window); delay action hydraulic closer; keyed handle

STATIONARY RAMP: optional. 24" L x 36" W x 3" H (610 mm L x 914 mm W x 76 mm H) aluminum stationary ramp with anti-skid tan powder coat.

WEIGHT OF UNIT:

- **DC battery-powered units:**
 - **Model VPL-3210B: 1210 lb (549 kg) (with batteries)**
 - **Model VPL-3212B: 1304 lb (591 kg) (with batteries)**
 - **Model VPL-3214B: 1400 lb (635 kg) (with batteries)**

- **All Models:**
 - Platform Gate Option: 80 lb (36 kg)**
 - Top Landing Gate Option: 99 lb (45 kg)**
 - Top Landing Wide Gate Option: 108 lb (49 kg)**

TESTING PERFORMED:

- 1) life cycle test performed at manufacturer's location
- 2) ASME A18.1/CSA B613-00 code tests performed at manufacturer's location

**Bruno Independent Living Aids, Inc., 1780 Executive Drive, P.O. Box 84, Oconomowoc, WI 53066
Phone (800) 882-8183 Fax (262) 953-5501**

Any reproduction or other use of these materials without written permission of Bruno Independent Living Aids, Inc. is expressly prohibited.
Bruno Independent Living Aids, Inc. reserves the right to modify or make changes to these specifications at any time without notice.

VPL Job Site Preparation

The following is a list of general operations designed to prepare the job site for installation of the VPL. This list is provided as a guide to help the installer. For a complete list of requirements check the installation site's applicable local codes.

Electrical Requirements:

- **DC battery-powered units:** require a dedicated GFCI 120V, 3A (max.), 60 Hz single-phase circuit to operate the internal battery charger. Check applicable local codes for all electrical and wiring requirements.

Platform Pathway Requirements:

Make sure the pathway that the platform runs in is clear of any electrical conduit and wire ways. Make sure no liquids, steam or gas piping discharge into the pathway, and make sure that there is sufficient headroom clearance (minimum of 80"– 2032 mm) throughout floor-to-floor travel. Make sure the area is sufficiently lit.

Floor Recommendations:

4" (102 mm) thick, 3500 PSI minimum compressive strength, reinforced concrete slab. Refer to technical drawings for minimum slab dimensions.

Floor Attachment:

VPL must be fastened to concrete slab using four (4) 1/2" (3/8" bolt) x minimum 2-1/2" long concrete anchors suitable for the environment. Refer to technical drawings for mounting hole locations. Follow selected concrete anchor manufacturer's guidelines and applicable codes.

Housing Attachment:

Use 5/16-18 tapped holes on tower frame work to fasten the tower housing to a vertical wall. Mounting brackets are supplied with unit. Note: Housing must remain intact.

Top Gate Attachment:

Refer to VPL gate technical drawing (see below).

Flush Mount Door Attachment:

Refer to VPL flush mount door detail drawing (see below).

Space Requirements:

Refer to VPL-3200B technical drawing (see below).

Platform-to-Top Landing Sill Clearance:

ASME code indicates the platform floor-to-sill clearance at the upper landing shall not be less than 3/8" (9.5 mm) nor exceed 3/4" (19 mm). Follow applicable local codes.

Fascia Wall Requirements:

ASME code indicates that fascia should be smooth and non-perforated that guards the full length and width of the platform. The fascia shall be securely fastened from the upper landing sill down to the lower landing sill. It should also be able to withstand a 125-pound side load over any 4-inch square area. Follow applicable local codes.

Technical Drawings (available at www.bruno.com):

- ILS-00932 Straight-Through Platform (No Pit)
- ILS-00933 Straight-Through Platform With Platform Gate (Pit Application)
- ILS-00934 90°/Adjacent Exit Platform (No Pit)
- ILS-00935 90°/Adjacent Exit Platform With Platform Gate (Pit Application)
- ILS-00938 Top Landing Gate Detail
- ILS-00980 Hoistway Straight-Through Platform (No Pit)
- ILS-00981 Hoistway Straight-Through Platform (Pit Application)
- ILS-00982 Hoistway 90°/Adjacent Exit Platform (No Pit)
- ILS-00983 Hoistway 90°/Adjacent Exit Platform (Pit Application)
- ILS-00984 Hoistway Same Side Platform (No Pit)
- ILS-00985 Hoistway Same Side Platform (Pit Application)
- ILS-01027 Flush Mount Door Detail

Bruno Independent Living Aids, Inc., 1780 Executive Drive, P.O. Box 84, Oconomowoc, WI 53066
Phone (800) 882-8183 Fax (262) 953-5501

Any reproduction or other use of these materials without written permission of Bruno Independent Living Aids, Inc. is expressly prohibited. Bruno Independent Living Aids, Inc. reserves the right to modify or make changes to these specifications at any time without notice.